



BUILT TOUGH, BUILT TO LAST, Since 1979

DROP SIDE DUMP BODY



Designed with the features you expect.

- Reliable and rugged scissor hoist, for proven load dumping of the heaviest materials
- Double acting pump (power up/power down)
- Bolt on subframe, hoist, and body for ease of installation, transfer, or replacement
- Easy release, locking pins for tailgate, top and bottom
- 10 Gauge construction throughout
- Stainless steel hinges w/ stainless pins
- LED lighting for visibility and less maintenance



****Shipped assembled on hoist & subframe***

SPECIFICATIONS

Length	Model	Sides	Cab to Axle (CA)	Inside Dimensions (L x W x H)	Body Width	Cubic Yards (level, + 6", + 6")	Hoist Capacity	Dump Angle	Weight w/o Cab Shield (lbs.)
9' - 3"	DEDH09396 DEDHS09396	13" Hinged	60" CA GM, FORD, RAM (min. 19,500 GVW)	111" x 86" x 13"	96"	2.6, 3.8, 5.1	8 ton Class 20	50°	2035 (painted) 1965 (SS)
11' - 3"	DEDH11396 DEDHS11396		84" CA GM, FORD, RAM (min. 19,500 GVW)	135" x 86" x 13"		3.2, 4.7, 6.2	9.5 ton Class 40		2320 (painted) 2250 (SS)
9' - 3"	DEDH09396-HD DEDHS09396-HD	18" Hinged	60" CA GM, FORD, RAM (min. 19,500 GVW)	111" x 86" x 18"		3.6, 4.8, 6.1	8 ton Class 20		2245 (painted) 2175 (SS)
11' - 3"	DEDH11396-HD DEDHS11396-HD		84" CA GM, FORD, RAM (min. 19,500 GVW)	135" x 86" x 18"		4.7, 6.2, 7.7	9.5 ton Class 40		2585 (painted) 2500 (SS)

*Cab shield weights vary (100-165 lbs)

GENERAL

- 10 gauge bed & body
- Dirt shedding, sloped design at side plates and top of tailgate
- Double panel side plates (painted: 10GA, stainless: 12GA)
- Dual pin latches each side, for safety and simplicity
- Full depth, 3/16" rear corner pillars incorporate recessed lighting, keyhole banjo eyes, and lower tailgate pin receiver
- All lighting is LED rubber mounted and NTEA & federal compliant
- All models are bolt on installation**
- 8" board extension pockets
- Self aligning rear latch release for the top gate pins
- Integrated tarp hooks
- Imron® Elite black oven cured paint w/ epoxy primer
- Two Year Limited Warranty**

TAILGATE

- Formed 10 gauge inner, outer, and end panels
- 1" hardened pins, (1" Stainless) with plasma cut latch receiving lock fingers
- Adjustable 1/4" chain for spreading aggregate material & holding gate in down position

FLOOR & UNDERSTRUCTURE

- 3" structural channel interlaced cross members (painted model)
- 3/16" formed 7" long sills (SS model only)
- Two piece, 10 gauge floor
- Bolt on sub frame & scissor hoist
- Greaseable bronze bearings for underbody release mechanisms (adjustable front & rear)

CAB SHIELD

- 12" (1/4 cab) overhang, standard
- Painted: 10GA, Stainless: 12GA
- Slotted dual windows
- 10 gauge side panels with pre punched tarp mounting provisions
- Straight overhang for ease of accessory installs

OPTIONS

- Stainless body construction**
- Tarp assembly, manual
- Coal chute (installed), painted or stainless
- Backup, running, or strobe lights in apron (painted model)

DownEaster

120 Old Lisbon Rd - Topsham, ME 04086

(207) 729-5101 - Fax: (207) 729-8782

www.downeastermfg.com

Member of:



Distributed by:



*Specifications subject to change without notice