

SWAP HOGG

www.SwapHogg.com



DESH 15E SERIES ROLL OFF SYSTEM



Shown with standard overhang for 84" CA



Shown with 12' tapered 11 yard body with 48" sides

SPECIFICATIONS - 15K ELECTRIC FRAME UNIT



Spring loaded auto locking latch



Polyurethane encased side rollers

STANDARD FEATURES

GENERAL

- * Low profile sub frame and mounting height
- * 6" bore x 15" stroke hoist, standard.
- * 50 deg. Dump angle (10 ton)
- * 6" x 2" structural tube frame.
- * Auto locking body latch w/ ergonomic pull handle.
- * Warn 15K electric industrial winch w/ tensioner
- * Polyurethane side & rear rollers pressed over DOM steel, w/ greaseable / replaceable 1045 shafts
- * Nylatron WP guide rails (replaceable)
- * Exterior mounted body prop
- * Stainless steel pump cover
- * Spacer plates between upper & lower frames minimizes rust contact points
- * "Winch-in" stop switch
- * Able to accept other body brands
- * 25' EIPS 1/2" cable w/ 4.5 ton hook
- * Stainless 304 rear guide plates
- * 4 button, in cab, control pendant
- * 1/0 GA battery cables w/ 600 amp fuse
- * **Imron**® Elite black oven cured paint w/ epoxy primer

AVAILABLE BODIES

- * 11 yard, 48" high side 12' tapered dumpster, no side pillars
- * 8 yard, 36" high side 12' tapered dumpster, no side pillars
(Available for above bodies: full width door, barn doors, and chipper top assembly.)
- * Dump body, 3-5 yard solid 13" high side w/ drive on gate
(18" high side w/ drive on gate also available)
- * Dump body, 3-5 yard, 13" drop Side
(dump bodies available in 304 stainless steel)
- * Platform body, 10' drive-on w/ external stake pockets & steel floor
- * Platform body, 11' straight deck w/ external stake pockets & steel floor
- * 12' Storage body w/ 6' walls, roof, & barn doors
- * **Subframe only for build your own body**

OPTIONS

- * Cab shield (for applicable bodies)
- * Spring loaded tarp system
- * Mud flap bracket kit (stainless)
- * Fuel filler neck bracket (stainless)
- * Poly fender kit
- * Hitch plate w/ receiver tube and adjustable pintle holes
- * Hitch plate light bar tube kit
- * Tarp tower, stationary
- * Spring loaded tarp system

IT IS HIGHLY RECOMMENDED THAT CLASS 6 AND UP TRUCKS USE THE DIRECT HYDRAULIC SYSTEM WITH PTO AND WINCH.

Distributed by: