




BUILT TOUGH, BUILT TO LAST, Since 1979

XD SERIES MED. DUTY



Available in 304 Stainless Steel construction.

Shown w/ options



Class 40, 50 & 70 hoists available



Shipped assembled on hoist & Sub Frame

DUMP BODY SPECIFICATIONS - SCISSOR HOIST XD SERIES

Length	Model	Fixed Sides	Cab to axle (CA)	GVW Range	Inside Dim. (I.D.) (L x W x H)	Mounting length	Body Width	Cubic Yards (level, + 6", + 6")	Hoist capacity	Dump Angle	Weight (lbs.)
10'	DED1096-XD	30"	96"	26K 33K	119.5" x 86" x 30"	118"	96	6.5, 7.6, 8.7	17 - 23 ton class 50-70	50	3820
	DED1096-HD	24"	84" - 96"	23K 26K	119.5" x 86" x 24"			5.4, 6.5, 7.6,	14 ton class 40		3150

STANDARD FEATURES

FIVE Year Limited Warranty

GENERAL

- * **ATSM 572 Grade 50 High Tensile** materials throughout inside of body
- * 10GA Grade 50 front panel with integral stiffener
- * Double panel side plates equal over 5/16" thickness.
- * 10GA outer side panels w/ 3 vertical braces per side
- * Full depth 3/16" rear corner pillars incorporate recessed lighting, keyhole banjo eyes and lower tailgate pin receiver.
- * Oval knockout in rear post, for flashing or turn signal lights
- * Dirt shedding , sloped design at side plate and tailgate top
- * 10" board extension pockets
- * Class 40 (single cylinder), 50 & 70 hoists available (dual cylinders)
- * Epoxy primer with Phosphate prewash
- * Mounting hardware and brackets provided
- * All lighting is LED rubber mounted and NTEA and Federal compliant.
- * **DuPont™ Imron® Elite black oven cured paint w/ epoxy primer**

FLOOR & UNDERSTRUCTURE

- * **3/16" Grade 50 floor** w/ radius corners & single weld seam
- * 9", 3/16" formed long sills w/ interlaced cross members
- * 4" x 5.7# Channel cross members w/ formed 3/16" cross members over hoist
- * Greasable *Bronze* bearings for underbody release mechanisms
- * Front handle tailgate release, standard
- * 1.50" dia. 4140 rear hinge pins, removable for service.
- * Mounted & painted Sub frame for ease of installation
- * Dual Safety Props

TAILGATE

- * **Formed 3/16" grade 50** inner panel, 3/16" outer and end panels.
- * 1 1/4" lower lock pins, with forged latch receiving lock fingers.
- * Adjustable 5/16" chain for spreading aggregate material & holding gate in down position.
- * Integrated tarp hooks
- * 1.50" dia. 4140 hinge pins

CAB SHIELD


- * **Bolt on, multi height position**, 10GA cab protector for ease of install & future optional / custom overhang.
- * 24" (1/2 cab) overhang, standard.
- * Pre punched tarp mounting provisions.
- * Pre punched oval cutouts for flashing lights on side & front facing

OPTIONS

- * **Stainless body construction**
- * Tarp assembly, manual or spring loaded w/ electric motor.
- * Coal chute(s), installed, painted or stainless
- * Air powered tailgate lock release cylinder
- * Electric over hydraulic pump
- * 12" spreader apron, bolt or weld on



Greasable latch bearings



Optional Air cylinder operated gate latch



Optional Coal chute / inspection door

Distributed by: